

# Low Smoke & Fume

## Copper Cable

# CQR

First choice for quality

A cable designed by CQR to meet all aspects of the European Construction Product Regulation (CPR) EN50575.

This cable has been independently tested and certified by an accredited test facility and has been awarded a CPR Euro classification.

CQR offer the Installer, Specifier and End User a quality cabling solution and piece of mind that the product will perform to specification in the event of a fire.

*DP Certificates available online for download*




- Suitable for any installation where signal integrity is essential
- 7 x 0.182mm Tinned Copper
- Low Smoke & Fume Jacket
- Screened or Unscreened
- Manufactured to BS4737-3.30:2015 Type 2
- Fully compliant with EN50575 'CPR'

*Also available with a PVC Sheath*

*Also available as a Low Smoke Zero Halogen BS4737-3.30:2015 Type 1*

### Available Cores



### Product codes

Code	Description
CAB6/WH/LSF/100	6 Cores LSF White 100m Reel
CAB8/WH/LSF/100	8 Cores LSF White 100m Reel
CAB8/WH/LSF/200	8 Cores LSF White 200m Reel
CAB8/WH/LSF/500	8 Cores LSF White 500m Reel
CABS8/WH/LSF/100	8 Cores Screen LSF White 100m Reel

### Technical data

Core:	7 x 0.182
Resistance:	94.6 Ohms/Km
AWG:	25
Conductor Material:	Tinned Copper
Conductor area:	0.182mm <sup>2</sup>
Max voltage:	50 volts
Sheathing:	LSF
Core insulation:	PVC
Operating temp:	70°C
Euroclass Rating:	E <sub>ca</sub>
SCREENED CABLE	
Drain wire:	Soft tinned copper
Screen:	Alu/Polyester Foil

rev. 3-11/2020



[www.cqr.co.uk](http://www.cqr.co.uk)

[info@cqr.co.uk](mailto:info@cqr.co.uk)

Sales: +(0)151 606 1000 Tech: +(0)151 606 6311

CQR Security Ltd, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK

Over 30 Years experience of alarm cable manufacturing in the United Kingdom

